



## High Power LED Film Viewer



### Features:

- **High Power LED Module**
- **External Dimmable control**
- **Footswitch to toggle between Operational and Standby**
- **Viewing window—80 x 380mm**
- **Viewer Dimension—500 x 170 x 60mm**
- **Low Heat**
- **Light weight**
- **Over Temperature protection.**
- **> 280,000 Lux**
- **Carry Bag**

4a Cartwright Street  
CE6  
Vanderbijlpark  
Gauteng  
South Africa

Phone: +27 16 931 3068  
Fax: 086 508 2374  
E-mail: [johannv@industronic.co.za](mailto:johannv@industronic.co.za)



## Technical Data

No.	Description	Sign	Condition	Min.	Typ.	Max.
1	Input Voltage (VAC)	V <sub>in</sub>		90 VAC 60 Hz	220 VAC 50 Hz	264 VAC 50 Hz
2	Input Current (mA)	I <sub>in</sub>	26V/3000mA	1000 Max		
3	Protection		Over Current	90 ~ 115%, Hiccup mode, Recovers Automatically		
			Short	Hiccup mode, Recovers Automatically		
4	Safety	Output To Input	3000 VAC 10mA @ 1 min			
			10M ohms / 500 VDC			
5	Environment	Operation	-10 ~ +50°C			
		Storage	-25 ~ +85°C			